

MATERIAL SAFETY DATA SHEET



SCM CORPORATION

COATINGS & RESINS DIVISION
CLID AVENUE
CLEVELAND, OHIO 44115
EMERGENCY TELEPHONE NO. (216) 826-5566

The information contained herein is based on data available at the time of preparation of this data sheet and which SCM Corporation believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. The SCM Corporation shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and users of this material.

1226

PAGE 1

SECTION I

CODE IDENTIFICATION 1226 DATE PRINTED 03/14/86
PRODUCT IDENTIFICATION RUSTMASTER SPRAY - CLEAR GLOSS

SECTION II - HAZARDOUS INGREDIENTS

| INGREDIENT | WEIGHT PERCENT | THRESHOLD LIMIT VALUE | LEL | VAPOR PRESS. |
|--------------------------|----------------|-----------------------|-----|--------------|
| TOLUENE | 40 | 100 PPM | 1.2 | |
| ACETONE | 20 | 750 PPM | 2.6 | |
| ETHYL-3-ETHOXYPROPIONATE | 5 | 50 PPM | 1.0 | |
| PROPANE - PROPELLANT | 15 | 1000 PPM | 2.3 | |
| ISOBUTANE - PROPELLANT | 15 | 1000 PPM | 1.8 | |

THE THRESHOLD LIMIT VALUE (TLV) IS THE TIME WEIGHTED AVERAGE (TWA) TO WHICH IT IS BELIEVED THAT MOST WORKERS MAY BE EXPOSED 8-10 HOURS PER DAY, 40 HOURS PER WEEK WITHOUT ADVERSE HEALTH EFFECTS.

LEL - THE LOWER EXPLOSIVE LIMIT IS THE LOWEST CONCENTRATION (% OF VOLATILES IN AIR) THAT WILL PRODUCE A FLASH OF FIRE WHEN AN IGNITION SOURCE IS PRESENT.

SECTION III - PHYSICAL DATA

BOILING RANGE NOT DETERMINED WEIGHT PER GALLON N.A.
% VOLATILE BY VOLUME 95.00

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (SETA) 20 F LOWER EXPLOSIVE LIMIT 1.0

DOT (PSN) CONSUMER COMMODITY ORM-D-AIR

MATERIAL SAFETY DATA SHEET



SCM CORPORATION

COVEN COATINGS & RESINS DIVISION
8000 LUDLOW AVENUE
CLEVELAND, OHIO 44115
EMERGENCY TELEPHONE NO. (216) 826-5566

The information contained herein is based on data available at the time of preparation of this data sheet and which SCM Corporation believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. The SCM Corporation shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and users of this material.

1226

PAGE 2

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

HAZARD CLASS FLAMMABLE LIQUID

EXTINGUISHING MEDIA

DRY CHEMICAL OR FOAM

UNUSUAL FIRE AND EXPLOSION HAZARDS

CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT OR FIRE.

VAPORS MAY IGNITE EXPLOSIVELY AT AMBIENT TEMPERATURES.

VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL LONG DISTANCES TO A SOURCE OF IGNITION AND FLASH BACK.

MAY DECOMPOSE UNDER FIRE CONDITIONS EMITTING IRRITANT AND/OR TOXIC GASES.

SPECIAL FIRE FIGHTING PROCEDURES

WATER MAY BE USED TO COOL AND PROTECT EXPOSED CONTAINERS.

SECTION V - HEALTH HAZARD DATA

ROUTE OF ENTRY INHALATION
 SKIN
 EYES
 INGESTION

EFFECTS OF OVEREXPOSURE

IRRITATION OF EYES, SKIN, RESPIRATORY TRACT. PROLONGED INHALATION MAY LEAD TO DIZZINESS AND/OR LIGHTEADEDNESS.

POSSIBLE NAUSEA, ANESTHETIC EFFECT OR NARCOSIS.

NOTICE - REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION

MOVE PERSON TO WELL VENTILATED AREA.

GET EMERGENCY MEDICAL ATTENTION.

ADMINISTER OXYGEN OR ARTIFICIAL RESPIRATION IF NECESSARY.

MATERIAL SAFETY DATA SHEET



SCM CORPORATION

GREEN COATINGS & RESINS DIVISION
10000 LICKLID AVENUE
CLEVELAND, OHIO 44115
EMERGENCY TELEPHONE NO. (216) 826-5566

The information contained herein is based on data available at the time of preparation of this data sheet and which SCM Corporation believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. The SCM Corporation shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and users of this material.

1226

PAGE 3

SECTION V - HEALTH HAZARD DATA

SKIN CONTACT FLUSH FROM SKIN WITH WATER, THEN WASH THOROUGHLY WITH SOAP AND WATER.

EYE CONTACT FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET EMERGENCY MEDICAL ATTENTION.

INGESTION GET EMERGENCY MEDICAL ATTENTION.

SECTION VI - REACTIVITY DATA

STABILITY STABLE

INCOMPATIBILITY *** NOT DETERMINED ***

CONDITIONS TO AVOID

*** NOT DETERMINED ***

HAZARDOUS DECOMPOSITION PRODUCTS

CARBON MONOXIDE
CARBON DIOXIDE

HAZARDOUS POLYMERIZATION

WILL NOT OCCUR

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

ELIMINATE ALL SOURCES OF IGNITION.
VENTILATE AREA WITH EXPLOSION-PROOF EQUIPMENT.
SMALL SPILLS MAY BE COLLECTED WITH ABSORBENT MATERIALS.
USE NON-SPARKING TOOLS.

WASTE DISPOSAL DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS.

MATERIAL SAFETY DATA SHEET



SCM CORPORATION

GREEN COATINGS & RESINS DIVISION
9 CLID AVENUE
CLEVELAND, OHIO 44115
EMERGENCY TELEPHONE NO. (216) 826-5566

The information contained herein is based on data available at the time of preparation of this data sheet and which SCM Corporation believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. The SCM Corporation shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and users of this material.

1226

PAGE 4

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION

CONTROL ENVIRONMENTAL CONCENTRATIONS BELOW APPLICABLE STANDARDS. WHERE RESPIRATORY PROTECTION IS REQUIRED, USE ONLY NIOSH/MSHA APPROVED RESPIRATORS IN ACCORDANCE WITH OSHA STANDARD 29 CFR 1910.134.

VENTILATION

PROVIDE DILUTION VENTILATION OR LOCAL EXHAUST TO PREVENT BUILD-UP OF VAPORS.
USE EXPLOSION-PROOF EQUIPMENT.
USE NON-SPARKING EQUIPMENT.

PERSONAL PROTECTIVE EQUIPMENT

EYE WASH
SAFETY SHOWER
SAFETY GLASSES OR GOGGLES
IMPERVIOUS GLOVES

SECTION IX - SPECIAL PRECAUTIONS

HANDLING AND STORAGE

STORE BELOW 80 F.
KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME.

OTHER PRECAUTIONS

USE ONLY WITH ADEQUATE VENTILATION.
DO NOT TAKE INTERNALLY.
KEEP OUT OF REACH OF CHILDREN.
AVOID CONTACT WITH SKIN AND EYES, AND BREATHING OF VAPORS.
WASH HANDS THOROUGHLY AFTER HANDLING, ESPECIALLY BEFORE EATING OR SMOKING.
KEEP CONTAINERS TIGHTLY CLOSED AND UPRIGHT WHEN NOT IN USE.